

> **MANDRINADORA CNC / CNC BORING MILLING MACHINE**

Fabricante	Manufacturer	<b>JUARISTI</b>
Modelo	Model	<b>TX-1</b>
Año	Year	<b>2007</b>
CNC	CNC	<b>HEIDENHAIN TNC-530</b>



**> FOTO ESTADO INICIAL:**

**> ESPECIFICACIONES TÉCNICAS / TECHNICAL SPECIFICATIONS**

<i>Superficie de la mesa:</i>	<i>Table Surface</i>	<b>Ø 1.300 mm.</b>
<i>Diámetro de la Caña:</i>	<i>Quill Diameter</i>	<b>125 mm.</b>
<i>Curso Longitudinal de Mesa (Eje X):</i>	<i>Table Longitudinal Traverse (X Axis)</i>	<b>2.000 mm.</b>
<i>Curso Transversal Columna (Eje W):</i>	<i>Column Cross Traverse (W Axis)</i>	<b>1.500 mm.</b>
<i>Curso Vertical (Eje Y):</i>	<i>Vertical Traverse (Y Axis)</i>	<b>2.000 mm.</b>
<i>Curso salida de caña (Eje Z):</i>	<i>Quill Exit Traverse (Z Axis)</i>	<b>600 mm.</b>
<i>Giro Mesa (Eje B)</i>	<i>Table Rotation (B Axis)</i>	<b>Continuo/ Continuos (0.001°)</b>
<i>Ejes Controlados</i>	<i>Controlled Axis</i>	<b>X, Y, Z, W, B</b>
<i>Cargador Automático de 30 Herramientas</i>	<i>Automatic Tool Charger: 30 tools</i>	<b>INCLUIDO/ INCLUDED</b>
<i>Evacuador de Virutas</i>	<i>Chip Conveyor</i>	<b>INCLUIDO/ INCLUDED</b>
<i>Sonda de Medida de Pieza</i>	<i>Measure Piece Probe</i>	<b>INCLUIDO/ INCLUDED</b>
<i>Refrigeración Externa de Herramienta</i>	<i>Tool External Coolant</i>	<b>INCLUIDO/ INCLUDED</b>
<i>Refrigeración Interna de Herramienta 20 BAR</i>	<i>Tool Internal Coolant 20 BAR</i>	<b>INCLUIDO/ INCLUDED</b>
<i>Carenado Total</i>	<i>Guarding Doors</i>	<b>INCLUIDO/ INCLUDED</b>
<i>Orientación de Eje Principal</i>	<i>Main Axis Orientation</i>	<b>INCLUIDO/ INCLUDED</b>
<i>Soporte de Salida Directa 350 mm</i>	<i>Direct Output Support 350 mm</i>	<b>INCLUIDO/ INCLUDED</b>
<i>Preparación Cabezal Automático 2,5° - 2,5°</i>	<i>Prepared for Automatic Head 2,5°- 2,5°</i>	<b>INCLUIDO/ INCLUDED</b>
<i>Avance Rápido Ejes:</i>	<i>Rapid Traverse</i>	<b>25.000 mm/min</b>
<i>Cono Interior Cabezal:</i>	<i>Taper Inside Head</i>	<b>ISO 50 DIN 69871/1-AD</b>
<i>Gama de Velocidades:</i>	<i>Turning Speds</i>	<b>2 Gamas /Ranges</b>
<i>Gama de Velocidades:</i>	<i>Range Speeds</i>	<b>0-3.000 rpm</b>
<i>Potencia de cabezal:</i>	<i>Head Power</i>	<b>30 Kw.</b>
<i>Peso Admisible sobre mesa MG X6</i>	<i>Table Carrying load MG X6</i>	<b>6.000 kg.</b>
<i>Peso de la Máquina:</i>	<i>Machine Weight</i>	<b>35.000 kg.</b>
<i>Volante Portatil</i>	<i>Portable Handwheel</i>	<b>HEIDENHAIN HR-410</b>
<i>Cabezal Alargador:</i>	<i>Extensible Head</i>	<b>INCLUIDO/ INCLUDED</b>
<i>Color de la Máquina</i>	<i>Machine Colour</i>	<b>RAL 7035 / RAL 5015</b>
<i>Estado de la Máquina</i>	<i>Machine Condition</i>	<b>EXCELENTE/ EXCELLENT</b>