

**> TALADRO RADIAL / RADIAL DRILL**

Fabricante	Manufacturer	<b>SORALUCE</b>
Modelo	Model	<b>TR2- 1600</b>


**> ESPECIFICACIONES TÉCNICAS / TECHNICAL SPECIFICATIONS**

Ø Máximo de Taladrado	Maximum Drilling Ø	<b>80 mm</b>
Diámetro de la Columna	Column Ø	<b>380 mm</b>
Brazo útil desde borde columna	Arm Length	<b>1639 mm</b>
Distancia máxima husillo-base	Maximum Distance Spindle of base	<b>1575 mm</b>
Cono Morse	Morse Taper	<b>Nº 5</b>
Motor del Husillo	Spindle Motor	<b>7,5 CV</b>
Nº de Velocidades	Speeds	<b>12 Velocidades/ Speeds</b>
Gama de rpm	RPM Range	<b>24-1400 rpm</b>
Nº de Avances	Feeds	<b>6 Avances/ Feeds</b>
Gama de Avances	Feeds Range	<b>0.05 – 0,33 mm/rpm</b>
Mesa Cúbica	Cubic Table	<b>INCLUIDA/ INCLUDED</b>
Dimensiones Mesa Cúbica	Cubic Table Dimensions	<b>1250x900x500 mm</b>
Superficie de la Base	Table Surface	<b>2530 x 1060 mm</b>
Peso de la Máquina	Machine Weight	<b>5000 Kg.</b>
Estado de la Máquina	Machine Conditions	<b>EXCELENTE/ EXCELLENT</b>